

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 Issue date: 2022-10-18 Revision date: 2022-10-18 Version: 1.0

## **SECTION 1: Identification**

Product form	: Mixture
Product name	: Dolomitic Hydrated Lime
Product code	: Not available
Product type	: Solid
Other means of identification	: Hydrated dolomitic lime (Ca(OH)2MgO), Double hydrated dolomitic lime (CaMg(OH)4) Dolomitic Hydrated Lime Type N
	Dolomitic Hydrated Lime Type S
	Dolomitic Hydrated Lime Type SA

Use of the substance/mixture

: Neutralization, flocculation, stabilization, polishing, masonry mortar, plaster, stucco, fresco paints and lime wash.

### 1.3. Supplier

#### Manufacturer

#### GRAYMONT #200-10991 Shellbridge Way Richmond, BC V6X 3C6 - Canada T 1 604 207-4292 - F 1 604 207-9014

Distributor Graymont Western US Inc 585 W Southridge Way Sandy, Utah 84070 - United States T +1 801-262-3942

#### 1.4. Emergency telephone number

Emergency number

: CHEMTREC, US (800-424-9300), INTERNATIONAL: (703-527-3887)

## SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS** classification

Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 1 Carcinogenicity Category 1A Specific target organ toxicity – Single exposure, Category 3 Specific target organ toxicity – Repeated exposure, Category 1

#### 2.2. GHS Label elements, including precautionary statements

### **GHS** labelling

Hazard pictograms (GHS)

Signal word (GHS) Hazard statements (GHS)

: Danger

: Causes skin irritation. Causes serious eye damage. May cause respiratory irritation.

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

	May cause cancer (Inhalation).
	Causes damage to organs (lungs) through prolonged or repeated exposure.
Precautionary statements (GHS)	: Obtain special instructions before use.
	Do not handle until all safety precautions have been read and understood.
	Do not breathe dust/fume/gas/mist/vapours/spray.
	Wash hands, forearms and face thoroughly after handling.
	Do not eat, drink or smoke when using this product
	Use only outdoors or in a well-ventilated area.
	Wear protective gloves/protective clothing/eye protection/face protection.
	If exposed or concerned: Get medical advice/attention.
	If on skin: Wash with plenty of water.
	Take off contaminated clothing and wash it before reuse.
	If skin irritation occurs: Get medical advice/attention.
	If inhaled: Remove person to fresh air and keep comfortable for breathing.
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
	Immediately call a poison center or doctor.
	Store in a well-ventilated place. Keep container tightly closed.
	Store locked up.
	Dispose of contents/container to hazardous or special waste collection point, in accordance with
	local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

#### No additional information available

2.4. Unknown acute toxicity

Not applicable

### **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

#### Not applicable

### 3.2. Mixtures

Name	um hydroxide Calcium hydroxide Calcium dihydroxide / Calcium hydroxide (Ca(OH)2) / Hydrated lime / Lime, hydrated / CALCIUM HYDROXIDE / Slaked lime		%	
Calcium hydroxide			50 – 75	
Magnesium oxide (MgO)			50 – 75	
Quartz	Quartz Quartz (SiO2) / Silica, crystalline, quartz / Crystalline silica, quartz / .alphaQuartz / Silica, crystalline, .alphaquartz / QUARTZ / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystallinealpha.quartz / Silica, .alphaquartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	CAS-No.: 14808-60-7	0.0001 – 1	

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Comments

: Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source.

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If a generic chemical name is shown and/or the CAS number is not disclosed, the specific chemical identity has been withheld as a trade secret.

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general First-aid measures after inhalation	<ul> <li>IF exposed or concerned: Get medical advice/attention.</li> <li>If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.</li> </ul>
First-aid measures after skin contact	<ul> <li>IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.</li> </ul>
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and ef	fects (acute and delayed)
Symptoms/effects after inhalation Symptoms/effects after skin contact	<ul> <li>May cause irritation to the respiratory tract.</li> <li>Causes skin irritation. May cause burns in the presence of moisture. Symptoms may include redness, drying, defatting and cracking of the skin. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.</li> </ul>
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
	diamica.

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures				
5.1. Suitable (and unsuitable) extinguishing media				
Suitable extinguishing media Unsuitable extinguishing media	<ul><li>: Use extinguishing media appropriate for surrounding fire.</li><li>: Do not use water jet.</li></ul>			
5.2. Specific hazards arising from th	ne chemical			
Fire hazard : None.				
5.3. Special protective equipment and precautions for fire-fighters				
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).			

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 6: Accidental release meas	sures		
6.1. Personal precautions, protective equipment and emergency procedures			
General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny ent unnecessary and unprotected personnel.			
<ul><li>6.1.1. For non-emergency personnel</li><li>No additional information available</li><li>6.1.2. For emergency responders</li><li>No additional information available</li></ul>			
6.2. Environmental precautions			
Prevent entry to sewers and public waters.			
6.3. Methods and material for containment and cleaning up			
For containment Methods for cleaning up	<ul> <li>Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).</li> <li>Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Provide ventilation. Avoid dust formation.</li> </ul>		
6.4. Reference to other sections			
For further information refer to section 8: "Exposure controls/personal protection".			

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage				
7.1. Precautions for safe handling				
Precautions for safe handling Hygiene measures	<ul> <li>Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Avoid generating dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Good housekeeping is important to prevent accumulation of dust. Wear appropriate PPE (see Section 8).</li> <li>Wash contaminated clothing before reuse. Always wash hands after handling the product.</li> </ul>			
7.2. Conditions for safe storage, including a	ny incompatibilities			
Storage conditions	: Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a well- ventilated place. Store in dust-tight, dry, labelled containers. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.			

## SECTION 8: Exposure controls/personal protection

8.1. Control parameters			
Dolomitic Hydrated Lime			
No additional information available			
Calcium hydroxide (1305-62-0)			
Canada (Alberta) - Occupational Exposure Limits			
OEL TWA 5 mg/m <sup>3</sup>			

# Safety Data Sheet

Calcium hydroxide (1305-62-0)				
Canada (Quebec) - Occupational Exposure Limits				
VEMP (OEL TWA) 5 mg/m <sup>3</sup>				
Canada (British Columbia) - Occupational Exposure Limits				
OEL TWA 5 mg/m <sup>3</sup>				
Canada (Ontario) - Occupational Exposure Limits				
OEL TWA 5 mg/m <sup>3</sup>				
Canada (Saskatchewan) - Occupational Exposure Limits				
OEL TWA 5 mg/m <sup>3</sup>				
OEL STEL 10 mg/m <sup>3</sup>				
USA - ACGIH - Occupational Exposure Limits				
ACGIH OEL TWA 5 mg/m <sup>3</sup>				
USA - OSHA - Occupational Exposure Limits				
OSHA PEL TWA [1] 15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)				
USA - NIOSH - Occupational Exposure Limits				
NIOSH REL TWA 5 mg/m <sup>3</sup>				
USA - MSHA - Occupational Exposure Limits				
MSHA PEL TWA 8/40 h	5 mg/m³			
Magnesium oxide (MgO) (1309-48-4)				
Canada (Alberta) - Occupational Exposure Limits				
OEL TWA 10 mg/m³ (fume)				
Canada (Quebec) - Occupational Exposure Limits				
VEMP (OEL TWA) 10 mg/m³ (inhalable dust)				
Canada (British Columbia) - Occupational Exposure Limits				
	Limits			
	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume)			
	10 mg/m³ (fume, inhalable)			
	10 mg/m³ (fume, inhalable) 3 mg/m³ (respirable dust and fume)			
OEL STEL Canada (Ontario) - Occupational Exposure Limits	10 mg/m³ (fume, inhalable) 3 mg/m³ (respirable dust and fume)			
OEL STEL Canada (Ontario) - Occupational Exposure Limits	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (inhalable particulate matter)			
OEL STEL Canada (Ontario) - Occupational Exposure Limits OEL TWA Canada (Saskatchewan) - Occupational Exposure Lim	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (inhalable particulate matter)			
OEL STEL Canada (Ontario) - Occupational Exposure Limits OEL TWA Canada (Saskatchewan) - Occupational Exposure Li OEL TWA	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (inhalable particulate matter) mits			
OEL STEL Canada (Ontario) - Occupational Exposure Limits OEL TWA Canada (Saskatchewan) - Occupational Exposure Li OEL TWA	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (inhalable particulate matter) mits 10 mg/m <sup>3</sup> (inhalable fraction)			
OEL STEL         Canada (Ontario) - Occupational Exposure Limits         OEL TWA         Canada (Saskatchewan) - Occupational Exposure Li         OEL TWA         OEL STEL         USA - ACGIH - Occupational Exposure Limits	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (inhalable particulate matter) mits 10 mg/m <sup>3</sup> (inhalable fraction)			
OEL STEL         Canada (Ontario) - Occupational Exposure Limits         OEL TWA         Canada (Saskatchewan) - Occupational Exposure Limits         OEL TWA         OEL TWA         OEL STEL         USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA	10 mg/m³ (fume, inhalable) 3 mg/m³ (respirable dust and fume) 10 mg/m³ (respirable dust and fume) 10 mg/m³ (inhalable particulate matter) mits 10 mg/m³ (inhalable fraction) 20 mg/m³ (inhalable fraction)			
OEL STEL         Canada (Ontario) - Occupational Exposure Limits         OEL TWA         Canada (Saskatchewan) - Occupational Exposure Limits         OEL TWA         OEL STEL         USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (respirable dust and fume) 10 mg/m <sup>3</sup> (inhalable particulate matter) mits 10 mg/m <sup>3</sup> (inhalable fraction) 20 mg/m <sup>3</sup> (inhalable fraction) 10 mg/m <sup>3</sup> (inhalable particulate matter)			

# Safety Data Sheet

Magnesium oxide (MgO) (1309-48-4) USA - IDLH - Occupational Exposure Limits				
	750 mg/m³ (fume)			
USA - MSHA - Occupational Exposure Limits				
MSHA PEL TWA 8/40 h 10 mg/m <sup>3</sup> (inhalable particulate matter)				
Quartz (14808-60-7)				
Canada (Alberta) - Occupational Exposure Limits				
Local name	Silica-Crystalline: Quartz			
OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate)			
Notations and remarks	Carcinogenicity A2			
Regulatory reference	reference Alberta Regulation 191/2021			
Canada (Quebec) - Occupational Exposure Limits				
VEMP (OEL TWA) 0.1 mg/m <sup>3</sup> (respirable dust)				
Canada (British Columbia) - Occupational Exposure Limits				
Local name Silica, Crystalline - alpha quartz				
OEL TWA	0.025 mg/m³ (respirable)			
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen			
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)			
Canada (Ontario) - Occupational Exposure Limits				
OEL TWA	0.1 mg/m <sup>3</sup> (designated substances regulation-respirable fraction (Silica, crystalline)			
Canada (Saskatchewan) - Occupational Exposure Limits				
OEL TWA 0.05 mg/m <sup>3</sup> (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)				
USA - ACGIH - Occupational Exposure Limits				
Local name Silica crystaline - quartz				
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate matter)			
Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger				
ACGIH chemical category Suspected Human Carcinogen				
Regulatory reference ACGIH 2022				
USA - OSHA - Occupational Exposure Limits				
Local name	Quartz (Total Dust) (Silica: Crystalline)			
OSHA PEL TWA [1]	50 μg/m³ (Respirable crystalline silica)			
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.			
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts			
USA - IDLH - Occupational Exposure Limits				
IDLH	50 mg/m <sup>3</sup> (respirable dust)			
USA - NIOSH - Occupational Exposure Limits				
NIOSH REL TWA	0.05 mg/m <sup>3</sup> (respirable dust)			

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Quartz (14808-60-7)				
USA - MSHA - Occupational Exposure Limits				
MSHA PEL TWA 8/40 h         30 mg/m³ / (%SiO2) + 2 mg/m³ (Total dust)           10 mg/m³ / (%SiO2) + 2 mg/m³ (Respirable dust)				
8.2. Appropriate engineering controls				
Appropriate engineering controls       : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.         Environmental exposure controls       : Avoid release to the environment.				
8.3. Individual protection measures/Personal protective equipment				
Hand protection:				
Wear suitable gloves resistant to chemical penetration				
Eye protection:				
Wear eye/face protection				
Skin and body protection:				
Wear suitable protective clothing				
Respiratory protection:				
n case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the				

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## **SECTION 9: Physical and chemical properties**

		9.1. Information on	basic physi	cal and chen	nical properties
--	--	---------------------	-------------	--------------	------------------

Physical state Appearance Colour Odour Odour threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butylacetate=1) Flammability Vapour pressure Relative vapour density at 20 °C / 68 °F Relative density Solubility Partition coefficient n-octanol/water Auto-ignition temperature	<ul> <li>Solid</li> <li>Powder.</li> <li>White</li> <li>Sweet</li> <li>No data available</li> <li>12.45 saturated solution at 25°C / 77 °F</li> <li>No data available</li> <li>No tapplicable</li> <li>2.2 - 2.6</li> <li>Water: 0.1 g/100ml at 20°C / 68 °F</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
5	: Not applicable
Decomposition temperature	: 345 °C / 653 °F
Viscosity, kinematic Viscosity, dynamic Explosive limits	: Not applicable : No data available : Not applicable

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Explosive properties	:	No data available
Oxidising properties	:	No data available

9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

**10.2. Chemical stability** 

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

**10.4. Conditions to avoid** 

Incompatible materials.

**10.5. Incompatible materials** 

Oxidizing materials. Acids. Reactive materials.

**10.6. Hazardous decomposition products** 

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (dermal)	Not classified. Not classified. Not classified.
Calcium hydroxide (1305-62-0)	
LD50 oral rat	7340 mg/kg
LD50 dermal rat	> 2500 mg/kg
LC50 inhalation rat	> 6.04 mg/l/4h
ATE CA (oral)	7340 mg/kg bodyweight
Magnesium oxide (MgO) (1309-48-4)	
LD50 oral rat	3870 mg/kg
ATE CA (oral)	3870 mg/kg bodyweight
	Causes skin irritation. pH: 12.45 saturated solution at 25°C / 77 °F
Serious eye damage/irritation :	, Causes serious eye damage.
	pH: 12.45 saturated solution at 25°C / 77 °F Not classified.
Germ cell mutagenicity :	Not classified.
Carcinogenicity	May cause cancer if inhaled. Risk of cancer depends on duration and level of exposure.

# Safety Data Sheet

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity :	Not classified.
STOT-single exposure :	May cause respiratory irritation.
Calcium hydroxide (1305-62-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure :	Causes damage to organs through prolonged or repeated exposure.
Quartz (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard :	Not classified.
Dolomitic Hydrated Lime	
Viscosity, kinematic	Not applicable
Symptoms/effects after inhalation :	May cause irritation to the respiratory tract.
Symptoms/effects after skin contact :	Causes skin irritation. May cause burns in the presence of moisture. Symptoms may include redness, drying, defatting and cracking of the skin. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Symptoms/effects after eye contact :	Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion :	May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms :	May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Other information :	Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general : I	No known significant effects or critical hazards.
12.2. Persistence and degradability	
Dolomitic Hydrated Lime	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
Dolomitic Hydrated Lime	
Partition coefficient n-octanol/water	Not applicable
Bioaccumulative potential	Not established.
Calcium hydroxide (1305-62-0)	
BCF - Fish [1]	(no bioaccumulation)

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29	9 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Other information	: No other effects known.
SECTION 13: Disposal considerations	
13.1. Disposal methods	
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
SECTION 14: Transport information	
In accordance with DOT / TDG / IMDG / IATA	
14.1. UN number	
Not regulated for transport	
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT)	: Not applicable
<b>TDG</b> Transport hazard class(es) (TDG)	: Not applicable
IMDG Transport hazard class(es) (IMDG)	: Not applicable
IATA Transport hazard class(es) (IATA)	: Not applicable
14.4. Packing group	
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
Special transport precautions	: Do not handle until all safety precautions have been read and understood.

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

#### DOT No d

No data available

### TDG

No data available

#### IMDG

No data available

#### ΙΑΤΑ

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

#### **15.1. US Federal regulations**

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

#### 15.2. International regulations

#### No additional information available

#### 15.3. US State regulations

**WARNING:** This product can expose you to Silica, respirable crystalline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Calcium hydroxide(1305-62-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
Magnesium oxide (MgO)(1309-48-4)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
Quartz(14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List

### **SECTION 16: Other information**

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

#### Revision date Other information

Prepared by

- None.
   Nexreg Compliance Inc. www.Nexreg.com

: 10/18/2022



## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Full text of H-statements	
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

SDS HazCom 2012 - WHMIS 2015 (Nexreg) - Section 15 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.